

HINGED DOORS

DURABLE FULLY ENGINEERED HINGED DOOR, DESIGNED FOR AMBIENT, CHILL AND FREEZER APPLICATIONS

- ROBUST CONSTRUCTION
- HYGIENIC AND FOODSAFE
- SPECIFICATION TO SUIT CUSTOMER REQUIREMENTS
- BASED ON FULL RANGE OF FERMOD FITTINGS
- AVAILABLE IN A WIDE RANGE OF COLOURS AND FINISHES
- COMPREHENSIVE WARRANTY PACKAGES

TECHNICAL & SPECIFICATION

- HANDLE - Available with the complete range of Fermod non-locking and locking fasteners for example 621, 920 (Standard), 921, 1220, 1221 & 1216 dependant on the weight and intended application
- HINGE - Any selection from the full Fermod range e.g. 1573HP as standard dependant on weight and intended application.
- TYPE - Suitable for ambient, chill, freezer and blast freezer application.
- LEAF - Single or double

FRAME & DOOR SURROUND CHANNEL OPTIONS

- Anodised aluminium finish as standard.
- Powder coated aluminium
- 304 grade stainless steel

FRAME TYPE

- Face mounted complete with door reveal linings and nylon fixing bolts

HEATERS

- Low voltage frame and hreshold heaters supplied as standard on all low temperature doors
- Heaters can also be incorporated within the door leaf if so required.

GASKET

- Fermod double row

INSULATED CORE

- 40mm, 80mm or 100mm thick PIR

DOOR LEAF FINISH

- White Foodsafe Laminate internal and external as standard
- Full range of Corus HP200, HPS200 standard steels
- 304 grade stainless steel
- PVC or GRP

LOCKS

- Full Fermod range all with internal safety release
- Panic bar/ push pad with or without external override
- Kingpin or Redlam bolt
- Hasp & Stape with internal safety release

FITTINGS

- Vision panel single or dual glazed

KICK PLATES

- Profiled aluminium, 304 grade stainless steel, PVC or GRP



SALES HOTLINE

0845 094 4060

